



MODEL YEAR 2026 | CVO™ STREET GLIDE 3 LIMITED®

Dimensions	FLHLTSE CVO™ Street Glide® 3 Limited
Length (*Cert)	105.7 in. (2,685 mm)
Overall Width (*Cert)	57.3 in. (1,455 mm)
Overall Height (*Cert)	56.5 in. (1,435 mm)
Seat Height, Laden	27.3 in. (693 mm)
Seat Height, Laden (Low seat position)	
Seat Height, Laden (High seat position)	
Seat Height, Laden (Low seat position with optional ARH suspension)	
Seat Height, Laden (High seat position with optional ARH suspension)	
Seat Height, Unladen (*Cert)	28.9 in. (735 mm)
Seat Height, Unladen (Low seat position)	
Seat Height, Unladen (High seat position)	
Seat Height, Unladen (Low seat position with optional ARH suspension)	
Seat Height, Unladen (High seat position with optional ARH suspension)	
Static Ground Clearance (*Cert)	5.1 in. (130 mm)
Static Ground Clearance without ARH (*Cert)	
Static Ground Clearance with ARH (*Cert)	
Dynamic Ground Clearance (with optional suspension)	
Rake (steering head) (deg)	26
Fork Angle (deg)	32
Trail	3.8 in. (96 mm)
Wheelbase (*Cert)	67.7 in. (1,720 mm)
Tires, Type	Dunlop® Harley-Davidson Series, bias blackwall front and radial blackwall rear
Tires, Front Model	D408F
Tires, Front Specification	130/60B19 M/C 61H

Tires, Rear Model	TK100
Tires, Rear Specification	P215/45R18 83T
Fuel Capacity	6 gal. (22.7 l)
Reserve Fuel Capacity, Fuel Injection (warning light)	1 gal. (3.8 l)
Oil Capacity (w/filter)	5 qt. (4.7 l)
Transmission Capacity	1.22 qts. (1.15 l)
Primary Chain Case Capacity	1.1 qts. (1 l)
Coolant Capacity	0.82 qt. (0.78 l)
Weight, As Shipped (*Cert)	1,243 lb. (564 kg)
Weight, In Running Order (*Cert)	1,283 lb. (582 kg)
Gross Vehicle Weight Rating (*Cert)	1,700 lb. (771 kg)
Gross Axle Weight Rating, Front (*Cert)	511 lb. (232 kg)
Gross Axle Weight Rating, Rear (*Cert)	1,189 lb. (539 kg)
Luggage Capacity -Volume	7.1 cu ft (0.201 m ³)

Engine	FLHLTSE CVO™ Street Glide® 3 Limited	
Engine	Milwaukee-Eight® VVT 121	
Valves	Pushrod-operated, overhead valves with hydraulic, self-adjusting lifters; four valves per cylinder	
Bore (*Cert)	4.075 in. (103.5 mm)	
Stroke (*Cert)	4.625 in. (117.5 mm)	
Displacement (*Cert)	121 cu in (1,977 cc)	
Compression Ratio (*Cert)	11.4:1	
Fuel System	Electronic Sequential Port Fuel Injection (ESPI)	3
Air Cleaner	Synthetic Felt, Washable	
Exhaust	2-1-2 dual exhaust	
Lubrication System	Pressurized, dry-sump	

Drivetrain	FLHLTSE CVO™ Street Glide® 3 Limited
Primary Drive (*Cert)	Chain, 34/46 ratio
Final Drive (*Cert)	Belt, 30/70 ratio
Clutch	Mechanically actuated 10 plate wet, Assist and Slip

Transmission	6 Speed Cruise Drive w/ Reverse
Gear Ratios (overall) 1st (*Cert)	10.534
Gear Ratios (overall) 2nd (*Cert)	7.302
Gear Ratios (overall) 3rd (*Cert)	5.423
Gear Ratios (overall) 4th (*Cert)	4.392
Gear Ratios (overall) 5th (*Cert)	3.742
Gear Ratios (overall) 6th (*Cert)	3

Chassis	FLHLTSE CVO™ Street Glide® 3 Limited	
Frame	Mild steel, square-section backbone with twin downtubes	
Swingarm	Permanent mold cast aluminum	
Front Fork	1.9 in (49mm) dual bending valve	
Front Fork, Optional		
Rear Shocks	Hand-adjustable emulsion rear suspension	
Rear Shocks, Optional		
Wheels, Optional Style Type	N/A	4
Wheels, Front Type	Dual Grain, Chrome, 14-spoke	4
Wheels, Front Diameter	19 in. (483 mm)	
Wheels, Front Width	3.5 in. (89 mm)	
Wheels, Rear Type	Dual Grain, Chrome, 14-spoke	4
Wheels, Rear Diameter	18 in. (457 mm)	
Wheels, Rear Width	7 in. (178 mm)	
Brakes, Caliper Type	Front: 32 mm 4 piston fixed, Rear: floating 36 mm piston integrated park brake	
Brakes, Rotor Type	Dual floating rotors (front), fixed rotor (rear)	
Brakes, Front Diameter	11.8 in. (300 mm)	
Brakes, Front Thickness	0.197 in. (5 mm)	
Brakes, Front is dual	Yes	
Brakes, Rear Diameter	11.8 in. (300 mm)	
Brakes, Rear Thickness	0.276 in. (7 mm)	
Brakes, Anti-Lock Braking System (ABS)	Standard	
Suspension Travel, Front	4.6 in. (117 mm)	
Suspension Travel, Rear	3.46 in. (88 mm)	

Performance	FLHLTSE CVO™ Street Glide® 3 Limited	
Engine Torque Testing Method (*Cert)	J1349	
Engine Torque (*Cert)	138 ft-lb (187 Nm)	5
Engine Torque (rpm) (*Cert)	3,750	
Power (Hp/kW) (*Cert)	114 HP / 85 kW @ 4500 rpm	
Lean Angle Testing Method	N/A	
Lean Angle, Right (deg.)	N/A	
Lean Angle, Left (deg.)	N/A	

Electric	FLHLTSE CVO™ Street Glide® 3 Limited
Battery	Sealed, maintenance-free, 12V, 28-amp/hour, 405 cca (per battery Council International Rating)
Charging	Three Phase, 48-amp system (600W@13V, 2000 rpm, 625W max power @ 13V)
Starting	1.6kW electric with solenoid shift starter motor engagement
Lights (as per country regulation), Headlamp	LED
Lights (as per country regulation), Tail/Stop	LED
Lights (as per country regulation), Front Signal Lights	LED
Lights, Rear Turn Signals	LED
Gauges	Digital gauges integrated within the display
Auxiliary Lamps	LED Fog Lamps integrated into Lower Fairings
Electric Power Outlet	15 Watt USB-C electric power accessory port in media storage box
GPS System	Yes, embedded navigation system with real-time traffic and weather via Wi-Fi Hotspot (Subscription required in the US)
Reverse	Electric reverse actuated by handlebar mounted hand controls

Fuel Economy	FLHLTSE CVO™ Street Glide® 3 Limited
Fuel Economy Testing Method	Estimated City/Hwy
Fuel Economy	39 mpg (6 l/100 km)

Infotainment	FLHLTSE CVO™ Street Glide® 3 Limited
Infotainment system	Skyline™ OS
Screen Size	12.3 in (312 mm)
Type	Full Color TFT
Watts Per Channel	50
Watts per Channel	125 (4) & 150 (2)
Speakers	6
Speaker Size	Two 6.5 in. (165 mm) fairing speakers, two 6.5 in. (165 mm) Tour-pak speakers, and two 6.5 in. (165 mm) lower fairing speakers
Headset Specifications (if equipped)	Harley-Davidson® Packtalk Edge wireless Bluetooth® headset
AM	Standard
FM	Standard
MW	N/A
LW	N/A
Weather Band (WB)	N/A
SD Card, Flash Drive and MP3 - via USB Connection	Supported
Hands-free Mobile Phone - via Bluetooth	Standard
Rider/Passenger Intercom	Standard (Passenger Headset Sold Separately); VOX is available for H-D headsets
Vehicle Information Screen (Air temperature, oil pressure and EITMS)	Standard
Text-to-Speech (TTS) Languages	Same as Languages list
USB	USB-C/MTP/Smartphone will work with any phone which has proper adapters to the connection located in the inner fairing storage
Phone Connectivity	Apple CarPlay (wireless or wired)
Bluetooth	Phone/Media Player, Headset
Navigation - via Bluetooth	

Rider Safety Enhancements	FLHLTSE CVO™ Street Glide® 3 Limited
Anti-lock Brake System (ABS)	Included
Electronic Linked Braking (ELB)	Included
Traction Control System (TCS)	Included

Drag-torque Slip Control System (DSCS)	Included
Vehicle Hold Control (VHC)	Included
Tire Pressure Monitoring System (TPMS)	Included
Wheel Lift Mitigation	N/A

Cornering Rider Safety Enhancements	FLHLTSE CVO™ Street Glide® 3 Limited
Cornering Enhanced Anti-lock Brake System (C-ABS)	Included
Cornering Enhanced Electronic Linked Braking (C-ELB)	Included
Cornering Enhanced Traction Control System (C-TCS)	Included
Cornering Drag-Torque Slip Control System (C-DSCS)	Included
Enhanced Lift Mitigation	N/A

Warranty And Service	FLHLTSE CVO™ Street Glide® 3 Limited
Warranty	24 months (unlimited mileage)
Service Interval	First 1,000 miles (1,600 km), every 5,000 miles (8,000 km) thereafter

Footnotes	FLHLTSE CVO™ Street Glide® 3 Limited
1	<p>Vehicles depicted may differ from vehicles manufactured and delivered. Specifications and prices listed may differ from specifications and prices of vehicles manufactured and delivered. All product descriptions (including depictions, specifications, dimensions, measurements, ratings and competitive comparisons) are based on available information at the time of publication. Although such descriptions are believed correct, errors and changes can occur and complete accuracy cannot be guaranteed. Harley-Davidson may make changes at any time to prices and specifications, and may change or discontinue models, without notice and without incurring any obligation. Attention: Vehicles in the configurations shown and many of the accessories</p>

	described in this catalog may not be available for sale or use in some locations. Please check with your dealer for complete product details and the latest information. All models feature 6-speed transmission (VRSC™ models and Sportster® models are 5-speed) and carbon fiber belt final drive; multi-plate clutch with diaphragm spring in oil bath; and 2-year unlimited mileage warranty.
2	Measurement reflects 180 lb. (81.7 kg) operator weight.
3	Recommended 91 octane or higher fuel (R+M)/2.
4	Standard and optional wheels may vary by country and region.
5	Values shown are nominal. Performance may vary by country and region.
6	See motorcycle owner's manual for complete details.
7	Inspections of certain systems and components are required at 2,500 mile (4,000 km) intervals. See Owner's Manual for full details.

©2026 H-D or its affiliates. HARLEY-DAVIDSON, HARLEY, H-D, and the Bar and Shield Logo are among the trademarks of H-D U.S.A., LLC. Third-party trademarks are the property of their respective owners.